



SOLIDA

Professionale / *Professional*

- LA MACINATURA CON DOSAGGIO NON È MAI STATA COSÌ PRECISA
- DOSER GRINDING HAS NEVER BEEN SO ACCURATE

DATI TECNICI / TECHNICAL DATA

Numero d'ordinazione	Order code	AE 65 V
Diametro macine	Grinding disc diameter	65 Ø mm
Materiale macine	Grinding disc material	Acciaio temperato Hardened steel
Tensione / Frequenza / Fase	Voltage / Frequency / Phase	100 V / 50 Hz / 1 100 V / 60 Hz / 1 220 - 240 V / 50 Hz / 1 220 - 240 V / 60 Hz / 1
Watt	Watt	220 - 240 V drive: 440 W 100 V drive: 510 W
Giri motore	RPM	1400 rpm (50 Hz) 1650 rpm (60 Hz)
Capacità macinazione	Grinding capacity	Regolabile / Adjustable 6-9 g/sec
Capacità tramoggia	Hopper capacity	1,2 kg
Dimensioni (L x A x P)	Dimensions (w x h x d)	195 x 578 x 387 mm
Peso netto	Net weight	12,2 kg (Without tamper) 12,5 kg (With tamper)
Peso di trasporto	Shipping weight	13,7 kg (Without tamper) 14,0 kg (With tamper)

Opzioni colore / Color options



ACCESSORI O VERSIONI A RICHIESTA / SPECIAL EQUIPMENT

Contacolpi	Shot counter
Pressino telescopico	Telescopic tamper
START/STOP automatico	Automatic START/STOP

CERTIFICAZIONI / LISTINGS / CERTIFICATIONS

CE
 Conforms to: EC/EN 60335-1 except IPX1
 IEC/EN 60335-2-64 except IPX1

Voltaggi speciali a richiesta / Other elec. specifications available on request

